



**AQUA
TILE™**
Slip-Resistant Flooring

MAINTENANCE GUIDE

Keep your Aqua Tile surface safe, clean, and beautiful for yours to come.

WEEKLY MAINTENANCE GUIDE (60 - 90 MINUTES)

In addition to daily cleaning, weekly maintenance follows a 3-week rotating cycle using alternative product types.



1

WEEKLY CLEANING BY 3-WEEK ROTATING CYCLE

Follow the Aqua Tile recommended 3-week cycle:

- Week 1 — Degreaser Cleaner
- Week 2 — Degreaser Cleaner
- Week 3 — Peroxide Cleaner
- Repeat - Return to Week 1 and continue the cycle

Apply the appropriate cleaner using a foamer attachment. Allow proper dwell time as directed on the product label

This rotation ensures effective removal of oils, organic soils, and biofilm buildup.

GENERAL TIPS

Clean regularly to maintain slip resistance and appearance.

Address spills and stains promptly.

Consistent maintenance extends the life of your Aqua Tile Surface

Allow the surface to air dry completely before reopening.

2

DEEP CLEANING PROCESS

Use the required equipment and follow the proper sequence:

1. Apply — Dispense cleaner as a foam and allow it to dwell on the surface for 2 to 10 minutes.
2. Agitate — Use a floor scrubber with a green turf pad or soft bristled brush to agitate,
3. Recover — Remove cleaning slurry using a wet vacuum or squeegee to drain.
4. Rinse — Rinse the area thoroughly with clean water using a hose and sprayer,

Allow the surface to air dry completely before reopening to foot traffic.

Ensure all chemical residue is recovered or rinsed away to prevent unwanted soil buildup.

AVOID THESE MISTAKES

Using pressures washers above 2,000 psi as they may cause tiles to be lifted

Scrubbing with metallic brushes & grit-coated pads

Using solvent-based strippers such as Acetone

Using bleach-based cleaners (undiluted)

3

FOCUS AREAS & SPECIAL ATTENTION

Pay special attention to areas where soils, oils, and contaminants accumulate:

- High-traffic zones, pool entries/exits, and around play features
- Locker rooms, restrooms, and shower areas
- Food service and kitchen areas
- Around drains, gutters, and edges

For hard water deposits or scale, use Mineral Deposit Removers as a spot treatment wherever buildup is visible.

4

INSPECT & PREVENT

During weekly maintenance, inspect the installation for:

- Seams or edges: gap wider than 1/16", loose/lifting tiles, or moisture intrusion
- Surface condition: discoloration that may indicate chemical exposure
- Slip resistance: ensure the surface remains clean, free of residue, and safe.

Consistent inspection and cleaning help protect your flooring investment and ensure continued compliance with safety standards.



**AQUA
TILE™**
Slip-Resistant Flooring



[Aquatile.com](https://www.aquatile.com)



612-564-2003